

Betapure™ NT-T Series Filter Cartridges


The Next Generation in Depth Filter Technology

Betapure™ NT-T Series filter cartridges are 3M's latest advance in depth filtration technology. The all polypropylene filter is constructed using a design that utilizes flow enhancing filter media and an innovative flow pattern. The result is an absolute-rated filter with vastly superior on-stream life that provides more cost effective filtration than conventional melt-blown filter technologies. Betapure NT-T Series filter cartridges — the new leader in filtration performance.

Betapure NT-T Series Filter Construction

The Betapure NT-T Series cartridge was designed to provide significantly superior service life while maintaining a consistent filtration efficiency. Betapure NT-T Series filters achieve this through an innovative cartridge design that allows uniform distribution of fluid flow and contaminant throughout the entire depth of the cartridge. Betapure NT-T Series filter construction combines a polypropylene media with fluid distribution netting to form multiple layers. Critically positioned media flow channels allow greater movement of fluid from layer to layer. Three distinct media sections, made from multiple media/netting layers, are combined to form the filter cartridge.

Figure 1:
Betapure™ NT-T Series Media
Sections. Note that the actual
filter sections contain multiple
layers of media.



Applications

- **Chemical and Hydrocarbon Processing**
Acids, bleach (sodium hypochlorite), polyethylene & polypropylene manufacture, amine sweetening & water flood
- **Food and Beverage**
Bottled water particulate & turbidity reduction, reverse osmosis membrane & spray nozzle protection, diatomaceous earth or carbon fine trap & beverage blending, rinsing & wash water
- **Fine Chemical and Electronics**
Pre-RO filtration of high silt density index incoming water, copper sulfate plating bath filtration in printed circuit board construction and color screen filtration for CRT production
- **Coating**
Film & paper coatings, photo graphic film, lens coatings & can coatings, high quality paints & ink
- **Industrial**
Machine tool lubrication, chemicals, detergents, and waste water, textiles, plating baths, pulp & paper, process water & ground water remediation

Features & Benefits

Superior service life

- As much as 3 times greater dirt holding capacity than competitive filters.

All polypropylene depth filter cartridges

- Allow for broad chemical and temperature compatibility.

Ratings from 0.5 to 70 micron

- Suit a wide range of applications.

Absolute-rated performance

- Allows for consistent filtration quality.

Exhibits superior particle retention under increasing differential pressure



Cut-away of the Betapure™ NT-T Series filter cartridge showing the three sections of media layers and core

Betapure™ NT-T Series Filter Construction cont.

The outer and middle sections contain multiple layers of interleaved filter media and fluid distribution netting. Within each media layer a portion of the fluid travels through the media while the balance of the fluid is delivered directly to the next distribution layer through the flow channels. The fluid distribution netting provides longitudinal and latitudinal flow paths to evenly distribute fluid flow across the surface of each successive media layer.

The Difference is Performance

Flow channels appear in the outer and middle sections of the filter matrix, as seen in the cartridge cut-away. The size, number, and location of the flow channels combined with the fluid distribution netting ensure that a uniform amount of contaminant is distributed to each layer within these two sections, while maintaining a consistent flow.

The number of media flow channels decrease from the outer to middle sections to ensure even contaminant loading throughout the entire filter matrix. Extensive laboratory testing has demonstrated that 3M has developed the optimal filter cartridge design.

The inner section, supported by a rigid polypropylene core and equal to approximately one third of the filter’s depth, contains no flow channels and is the final qualifying section ensuring absolute rated performance.

The even distribution of contaminated fluid throughout the depth of the cartridge is the key to the Betapure NT-T Series filter’s exceptionally long service life, low pressure drops, and increased cost effectiveness.

The Result


Superior Filter Service Life

Extensive testing has demonstrated that competitive filters of equivalent removal ratings subjected to the same contaminant load plug more quickly than Betapure NT-T Series filters. The result is significantly shorter service life, and unpredictable filtration efficiencies. Betapure NT-T Series filters provide a service life improvement of up to 3 times greater than competitive products. (Graph 1)

Lower Pressure Drop

The design and construction of the Betapure NT-T Series cartridge allows for significantly lower pressure drops compared to equivalently rated polypropylene depth filters. Based on published data, a Betapure NT-T Series filter system with a given flow would use up to 75% fewer cartridges than Osmonics Selex, 68% fewer than Pall® Profile, and 42% fewer than Pall® Nexis. To underscore the Betapure NT-T Series filter cost benefit, use the example in Table 1 as a guideline.

Graph 1: Betapure™ NT-T Series Filters deliver longer service life



Betapure™ NT-T Series Filter Cartridges

Table 1: Comparison of 5 Micron* Filters in a 110 GPM System

	3M™ Betapure™ NT-T Series Filter	Pall Profile	Pall Nexis	Osmonics Selex
Flow (gpm) / 10" cartridge @ 1 psid	3.1	1.0	1.8	0.8
Number of filters for a 110 gpm flow rate	12 / 30" cartridges	37 / 30" cartridges	21 / 30" cartridges	43 / 30" cartridges

* Based on the manufacturers published rating.

For the same initial cartridge differential pressure, a 110 gpm system using Betapure NT-T™ Series filters require significantly fewer cartridges. This results in lower capital investment for the filter housing and fewer cartridges to purchase.

The Confidence of Consistency

Betapure™ NT-T Series filters utilize advanced design and construction to achieve a level of filtration consistency unattainable by competitive filters. Combined with an exceptionally long service life, the Betapure NT-T Series filter's consistent performance, as illustrated by comparative Beta-Ratio vs. Differential Pressure (Graph 2), provides predictable results throughout the filters' usable life. Filters A, B, and C show a degradation in the Beta-Ratio as psid increases. These filters exhibit a pattern of either unloading previously held particles or a loss of filtration efficiency. The result of this inconsistent performance is a reduction in finished product quality, product yield, and an increase in total filtration cost.

Absolute Rated Betapure NT-T Series

Consistent filtration performance, time after time, from start to finish is the goal of every filter user. Absolute removal ratings for Betapure NT-T Series filters are determined using a filter performance test developed by 3M to comply with the general procedures outlines in ASTM STP 975. 3M defines absolute rating as the particle size (x) providing an initial Beta Ratio (B_x) = 1000. At this Beta Ratio, the removal efficiency is equal to 99.9%. Betapure NT-T Series filter ratings are specified in Table 2.


Your Benefit — Total Filtration Cost Reduction

The Betapure NT-T Series filter's performance and superior life advantage allows direct cost savings by reducing the number of filters used. In addition, the resulting reduction in filter change-out frequency decreases direct labor and filter disposal costs. Betapure NT-T Series filter cartridges — providing performance and value.

Table 2: Betapure™ NT-T Series Filter Ratings

Grade Designation	Absolute Rating (µm)
T005	0.5 (extrapolated)
T010	1
T020	2
T030	3
T050	5
T100	10
T200	20
T300	30
T400	40
T500	50
T700	70

Graph 2: Beta Ratios demonstrate the Betapure™ NT-T Series filter's ability to perform consistently throughout its life





Betapure™ NT-T Series Filter Applications

Betapure NT-T Series' construction provides benefits to customers in a wide range of end-use filtration applications. High quality filtration along with total filtration cost reductions are very attractive benefits to customers in diverse industries.

Chemical and Hydrocarbon Processing

Cost reduction is the most critical issue in the production of high quality chemicals, petrochemicals, and in hydrocarbon processing. Using Betapure NT-T Series filters in demanding applications that require absolute-rated performance provides long service life, the consistency demanded to attain quality standards, and a total Filtration Cost reduction. Applications include:

- Acids, bleach (sodium hypochlorite)
- Polyethylene and polypropylene manufacture
- Amine sweetening and waterflood

Food & Beverage Applications

Increased consumer emphasis on product quality, as well as increased government regulation, are driving today's food & beverage industry to ever-finer levels of filtration. Betapure NT-T Series filter cartridges meet this challenge throughout their entire service life. Typical applications include:

- Bottled water particulate and turbidity reduction
- Reverse osmosis membrane and spray nozzle protection
- Diatomaceous earth or carbon fine trap
- Beverage blending, rinsing and wash water

Fine Chemical and Electronics

Betapure NT-T Series filters with their filter matrix are ideally suited for electronics applications where heavy contaminant loading is present and efficient long lasting filtration is required. The combination of all-polypropylene construction and the media provide the perfect filtration device for use in wafer manufacturing and semiconductor device fabrication. Applications include:

- Pre-RO filtration of high silt density index incoming water
- Copper sulfate plating bath filtration in printed circuit board construction
- Color screen filtration for CRT production

Coating

Betapure NT-T Series filter cartridges are well suited for the filtration of high solid coatings where they provide superior life while selectively removing the large undesired particles from the coating and allowing the smaller desired particles to pass. Betapure NT-T Series applications include:

- Film & paper coatings
- Photographic film
- Lens coatings
- Can coatings, high quality paints & ink

Industrial

Betapure NT-T Series filter cartridges are ideal for higher dirt loads because of the flow characteristics and long service life that provide reduced overall filtration costs. Betapure NT-T Series cartridges are used in a broad range of general industrial applications that include:

- Machine tool lubrication, chemicals, detergents, and waste water
- Textiles, plating baths
- Pulp & paper
- Process water & ground water remediation



3M Filter Housings

3M manufactures a broad variety of filter housings. Housings are available in a selection of materials and sizes that range from holding a single filter cartridge to hundreds. This breadth of design choice allows a match to your application requirements.

3M™ ES™ Series Filter Housing

The 3M ES Series filter housing is a durable, ASME Code designed, high volume filter housing. Conceived to maximize flexibility of design, it is available in carbon steel, 304L or 316L stainless steel and with variety of internal configurations to handle various filter cartridge formats. For more information, ask your local 3M Purification distributor for brochure 70-0201-8711-1.

3M™ CTG Series Filter Housing

The 3M CTG Series Filter design provides a totally enclosed system using separate pressure vessel and filter pack to isolate process fluid from the housing. This system greatly reduces the costs involved with filter change-out while protecting the environment and operator from exposure to the process fluid. For more information, ask your local 3M Purification distributor for brochure 70-0201-8693-1.

3M™ DC & SS Filter Housings

3M DC and SS filter housings offer a cost effective alternative for moderate volume filtration (up to 400 GPM). Constructed from 304L stainless steel (Model DC) or 316L stainless steel (Model SS), housings are available for a wide range of flow rates and applications. For more information ask for literature 70-0201-8757-4 and 70-0202-2106-8.



Table 3: Betapure™ NT-T Series Filter Specifications

Material of Construction <small>(All materials are FDA compliant per CFR 21)</small>	
Filter Media, Netting, Core, End Connector	Polypropylene
Gaskets and O-ring Options (see ordering guide)	Silicone, Fluorocarbon, EPR, Nitrile, Polyethylene
Filter Cartridge Dimensions	
Inside Diameter	1-3/32" nominal
Outside Diameter	2-1/2" nominal
Length	5, 9-3/4, 10, 19-1/2, 20, 29-1/4, 30, 39, 40 inches
Specification	
Maximum Operation Temperature	180°F (82°C)
Maximum Differential Pressure	50 psid (3.4 bar) @ 86°F (30°C) 30 psid (2.0 bar) @ 131°F (55°C) 15 psid (1.0 bar) @ 180°F (82°C)
Recommended Change-out Differential Pressure	35 psid (2.4 bar) @ 86°F (30°C)

Flow Rates

Detailed information for calculating flows for water and fluids with other viscosities is located in the following table. Use the formula in conjunction with the values from columns 3 or 4 in table 4. The specific pressure drop values may be effectively used when three of the four variables (viscosity, flow, differential pressure, and cartridge grade) are set.



Table 4: Betapure™ NT-T Series Filter Flow Rates

Grade	Absolute Rating (µm)	Specific Pressure Drop per 10" Cartridge	
		psid/gpm/cps	mbar/lpm/cps
T005	0.5	4.5	81.9
T010	1	2.5	45.5
T020	2	0.87	15.9
T030	3	0.44	8.0
T050	5	0.32	5.9
T100	10	0.14	2.5
T200	20	0.065	1.2
T300	30	0.05	0.91
T400	40	0.042	0.76
T500	50	0.029	0.52
T700	70	0.025	0.45

* Specific aqueous pressure drop at ambient temperature for a single length equivalent (10") cartridge. For multiple cartridge lengths, divide the total flow by the number of equivalent lengths. For liquids other than water, multiply the specific pressure drop value provided in the table by the viscosity in centipoise.

$$\begin{array}{l}
 \text{Clean} \\
 \Delta p \\
 \text{psi (mbar)}
 \end{array}
 = \frac{(\text{Total System gpm [lpm]}) (\text{Viscosity in Cp}) (\text{Value From Table})}{(\text{Number of Equivalent Single Length Cartridges in Housing})}$$

Chemical Compatibility

The 100% polypropylene construction provides excellent chemical compatibility in many demanding process fluid applications. Compatibility is influenced by process operating conditions: in critical applications, cartridges should be tested under actual conditions to ensure correct selection.

Application Engineering

3M Purification, Inc., Industrial Products has a global team of market-focused scientists and engineers who excel in supporting and collaborating with end-users. Our technical teams are skilled in performing on-site bench-scale or in-house tests, and relating results to full scale manufacturing operations and optimizing cost of purification. When unique processing problems are encountered, our product and application specialists are equipped to identify solutions using either 3M's broad array of existing products or potentially develop a custom solution for your application.

Service Worldwide

3M is a U.S. based multinational company with distribution and manufacturing sites worldwide. Global manufacturing sites together with trained stocking distributors and state-of-the-art laboratory facilities bring quality solutions to challenging filtration applications.


A Global, Diversified Technology Company

3M is fundamentally a science-based company. As a member of the 3M family, we create imaginative solutions, and we are a leading filtration provider in a wide range of markets, from the coarsest industrial filtration to the finest DNA separation. We provide the trusted solutions that our customers demand and expect. Our success is built on our ability to apply our technologies and expertise to an endless array of real-world customer needs. Virtually anywhere you go, 3M technologies are at work — making life easier and better for people around the world.



Betapure™ NT-T Series Ordering Guide

Cartridge Grade	Length (Inches)	Grade Code/ Rating (µm)	Packaging Option	Support Ring Option	End-modification	Gasket/O-ring Material
NT – Betapure NT-T Series	06† – 5	T005 0.5	S – Standard	For End Modification D, N, R O – None For End Modification B, C, F, M 1 – Polysulfone 2 – Stainless Steel O – None	B – 226 O-Ring with Spear C – 222 O-Ring with Spear D – DOE with Polypropylene End Caps F – 222 O-Ring with Flat Cap M – 222 O-Ring with Flat Cap** N – Unmodified DOE R – SOE, End Cap with Spring	For End Modification B, C, D, F, M, R A – Silicone B – Fluorocarbon C – EPR D – Nitrile For End Modification N, R G – Polyethylene
	09 – 9-3/4	T010 1				
	10 – 10	T020 2				
	19 – 19-1/2	T030 3				
	20 – 20	T050 5				
	29 – 29-1/4*	T100 10				
	30 – 30	T200 20				
	39 – 39*	T300 30				
	40 – 40	T400 40				
		T500 50				
	T700 70					



† Requires N end modification for use in CT101 (PN 44860) only.

* Applies to D and N end modifications only.

** For use with 1ZMP housing.

PLEASE NOTE: The Ordering Guide above is for reference only. Not all combinations are available. Please consult with your 3M Representative to determine the appropriate part number for your application.



This Betapure™ NT-T Series Filter is tested and certified by WQA against NSF/ANSI Standard 61 for material requirements only.*
 *For O-Ring "K" please consult factory.

Cold Water Only
 Install this product in accordance with the instructions provided by the housing manufacturer. This product has a minimum flow rate requirement of 6.6 gallons per day (25L per day).

NOTE: Configuration R and Gaskets/O-rings K are not listed with WQA.

Technical Information
The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.
Product Selection and Use
Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.
Warranty, Limited Remedy, and Disclaimer
Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.
Limitation of Liability
Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



Your local distributor:

3M Purification Inc.
 3M Separation and Purification Sciences Division
 400 Research Parkway
 Meriden, CT 06450 USA
 Phone 1-800-243-6894
 1-203-237-5541
 Fax 1-203-630-4530
 Web 3Mpurification.com

3M and Betapure are trademarks of 3M Company.
 All other trademarks are the property of their respective owners.
 © 2018 3M Company. All rights reserved.
 70020187202 REV 0318sr