

The JET-5<sup>™</sup> is ideal for air knife drying, vacuum, fluidized bed, cooling and exhaust applications. The JET-5<sup>™</sup> features belt-free DirectDrive<sup>™</sup> Technology (US & Int'l. Pat. Pend.), which is enabled by a proprietary high-speed motor and an aerodynamically designed blower. DirectDrive<sup>™</sup> enhances reliability and boosts performance by eliminating belts, tensioning devices and complex spindle assemblies common in other high-speedblowers. The JET-5<sup>™</sup> is engineered for moderate flow and moderate pressure applications from 30HP[22kW] to 40HP[30kW]. Its design and compact footprint enable it to fit into the widest range of OEM equipment.

## JET-5™



### **Advantages:**

- Efficient Power: The JET-5<sup>™</sup> is 10-12% more efficient than belt drive units. Available in 30-40HP or [22-30kW] ratings.


- Flow: 2200cfm [3738M3Hr]
- Pressure: 140"WG [350mBar]
- Vacuum: 120"WG [300mBar]


- **Ultra Compact:** Smallest footprint. One man install. Fed-Ex, DHL, and UPS delivery available. (See dimensions below.)

- **More Reliable:** Built-in motor protection. Ultra-balanced motor shaft. 1 year warranty and fewer parts.

- **Better ROI:** Most efficient energy use. No belts or adjustment costs. Lowest delivery costs.

- **Smart Control:** Variable Frequency Drive (VFD) control enables precise airflow settings, higher efficiencies, PLC connectivity, motor protection and nonspiking soft-starts.





1756 Eastman Ave., #100 Ventura, CA 93003 USA Phone: (805) 654-7000 Fax: (805) 654-7064



## Technical Specifications

### **DESCRIPTION:**

DirectDrive<sup>™</sup> Technology, Single Stage Centrifugal Compressor, Oil-Less, Spindle Free Design.

#### DRIVE SYSTEM:

DirectDrive<sup>™</sup> Technology, with Variable Frequency Drive Control. Integrated Motor Protection, Air Cooled Rated: 105°F[40°C] IMPELLER: 5 Axis C355 Aluminium

**AERO-BLOWER:** A356-T6 Aluminum with Integrated Lifting Eye.

HIGH-SPEED MOTOR: TEFC, IP54, External Junction Box, 30-40HP [22-30kW] 3-Phase, 390-480 and 600VAC, 50/60Hz, Thermister, 105°F [40°C] Ambient. WEIGHT: 180lbs.[82kg]

CONNECTIONS: Inlet 5"Ø [126mm], Outlet 4"Ø [102mm], 360° Rotation.

#### WARRANTY:

1 Year.

# Performance Curve: **JET-5**<sup>TM</sup>

